Safety Data Sheet

Product Name: UPHOLSTERY AND CARPET PROTECTOR

Creation Date: 08/04/19
Replaces: 08/08/16

SECTION 1: Identification of the substance/mixture and of the company undertaking

1.1. Product Identifier

SCOTTS UPHOLSTERY CLEANER
Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Upholstery and Carpet Protector

1.3. Details of the supplier of the safety data sheet

Scotts Trading
North Dorset Business Park
Rolls Mill Way, Sturminster Newton
Dorset, DT10 2GA
Tel: +44 (0)1305 260555
EM: **sales@scottstrading.com**

1.4. Emergency telephone number

0044 (0)1305 260555

SECTION 2: Hazards Identification

2.1 Classification of the substance or mixture

Classification (EC1272/2008)

Physical and chemical hazards: Flam. Aerosol 1 - H222

Human health: Skin Irrit. 2 – H315; STOT SE 3 – H336

Environmental: Aquatic Chronic 2 – H411

2.2 Label elements

Label in accordance with (EC) No. 1272/2008

Signal word: Danger.

Hazard statements:
H222: Extremely flammable aerosol.
H315: Causes skin irritation.
H336: May cause drowsiness or dizziness.
H411: Toxic to aquatic life with long lasting effects.

Precautionary statements:
P102: Keep out of reach of children.
P261: Avoid breathing vapour/spray.
P264: Wash contaminated skin thoroughly after handling.
P271: Use only outdoors or in a well-ventilated area.
P280: Wear protective clothing and gloves.
P304+P340: IF INHALED: remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312: Call a POISON CENTRE or doctor/physician if you feel unwell.
P332+P313: If skin irritation occurs: Get medical advice/attention.
P501: Dispose of contents/container in accordance with local regulations.

Supplementary precautionary statements:
P210: Keep away from heat/sparks/open flames/hot surfaces No smoking.
P211: Do not spray on an open flame or other ignition source.
P251: Pressurised container: Do not pierce or burn, even after use.
P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50ºC/122 ºF.

Supplemental label information

Contains:
SOL041: Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics,
H229: Pressurised container: May burst if heated.

2.3 Other hazards

SECTION 3: Composition/information on ingredients

3.2 Mixtures

BUTANE (Registration number: Exempt – Naturally occurring)

EC no:	CAS	Classification (67/548/EEC)	Classification (EC1272/2008)	Percent
203-448-7	106-97-8	F+; R12	Flam. Gas 1 - H220	10-30%

ISOBUTANE (Registration number: Exempt – Naturally occurring)

EC no:	CAS	Classification (67/548/EEC)	Classification (EC1272/2008)	Percent
200-857-2	75-28-5	F+; R12	Flam. Gas 1 - H220	5-10%

NAPHTHA (PETROLEUM), HYDRODESULPHURISED LIGHT DE-AROMATISED (Registration number: 01-2119475515-33-XXXX)

EC no:	CAS	Classification (67/548/EEC)	Classification (EC1272/2008)	Percent
927-510-4	64742-49-0	Xn;R65, Xi:R38, F;R11, N;R51/53, R67	Flam. Liq. 2 - H225; Skin Irrit. 2 – H315; STOT SE 3 - H336; Asp. Tox. 1 - H304; Aquatic Chronic. 2 - H411	60-100%

ODOURLESS KEROSENE (DUTY PAID)

EC no:	CAS	Classification (67/548/EEC)	Classification (EC1272/2008)	Percent
265-149-8	64742-47-8	Xn; R65, R66	Not classified.	<1%

The full test for all R-Phrases and Hazard statements are displayed in Section 16.

SECTION 4: First Aid Measures

4.1 Description of first aid measures

Contact with eyes: Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

Skin contact: Wash the skin immediately with soap and water. Get medical attention if any discomfit continues.

Ingestion: DO NOT INDUCE VOMITING! Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Get medical attention if any discomfort continues.

Inhalation: Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention.

General: Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting Measures

5.1. Extinguishing media

Suitable extinguishing media: Powder: Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

5.2. Special hazards arising from the substance or mixture

Unusual fire & explosion hazards: Aerosol cans may explode in a fire.

5.3 Advice for Fire fighters

Special firefighting procedures: Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

SECTION 6: Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures

6.2 Environmental precautions

6.3. Methods and material for containment and cleaning up

Methods for cleaning up: Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of explosion risk. If leakage cannot be stopped, evacuate area.

6.4. Reference to other sections

SECTION 7: Handling & Storage

7.1. Precautions for safe handling

Usage precautions: Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions: Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

7.3. Specific end use(s)

SECTION 8: Exposure Controls & Personal Protection

8.1. Control parameters Occupational exposure limits

Name	STD	TWA – 8 Hrs		STEL – 15 Min		Notes
BUTANE	WEL	600 ppm	1450 mg/m3	750 ppm	1810 mg/m3	
NAPHTHA(PETROLEUM), HYDRODESULPHURISED LIGHT, DE-AROMATISED			1000 mg/m3			
ODOURLESS KEROSENE (DUTY PAID)		165 ppm	1200 mg/m3			

WEL = Workshop Exposure Limit

8.2 Exposure controls

Protective equipment:

Engineering measures: Provide adequate general and local exhaust ventilation.

Respiratory protection: No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. Use chemical cartridge protection with appropriate cartridge.

Hand protection:	Use protective gloves.
Eye/face protection:	Use approved safety goggles or face shield.
Other protection:	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.
Hygiene measures:	DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

SECTION 9: Physical & Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance: physical state:	Aerosol.
Colour:	Typical.
Odour:	Characteristic.
Upper/lower flammability or explosive limits:	Lower: 0.8% - Upper 9%.

9.2. Other information

SECTION 10: Stability & Reactivity

10.1. Reactivity

10.2. Chemical stability

Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis, Strong mineral acids.

10.5 Incompatible materials

10.6. Hazardous decomposition products

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

SECTION 11: Toxicological Information

11.1. Information on toxicological effects – Acute toxicity - inhalation

Inhalation: May cause irritation to the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system. Irritating to respiratory system.

Ingestion: May cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach.

Skin contact: Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on skin. May cause cracking of skin, and eczema. May cause allergic contact eczema. May cause sensitisation by skin contact. Irritating to skin.

Eye contact: Irritating to eyes. May cause chemical eye burns.

Route of entry: Inhalation. Skin and/or eye contact.

SECTION 12: Ecological Information

Ecotoxicity: Dangerous for the environment if discharged into watercourses.

12.1. Toxicity

12.2. Persistence and Degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

General information: Empty containers must not be burned because of explosion hazard.

Disposal methods: Dispose of waste and residues in accordance with local authority requirements.

SECTION 14: Transport Information

14.1. UN number

UN No. (ADR/RID/ADN): 1950

UN No. (IMDG): 1950

UN No. (ICAO): 1950

14.2. UN proper shipping name

Proper shipping name: AEROSOLS.

14.3. Transport hazard class(es)

ADR/RID/ADN class: 2

ADR/RID/ADN class: Class 2: Gases

ADR label no: 2.1

IMDG class: 2.1

ICAO class/division: 2.1

Transport labels:

14.4. Packing group

ADR/RID/ADN packing group: Not Applicable

IMDG packing group: Not applicable.

ICAO packing group: Not applicable.

14.5 Environmental hazards

Environmentally hazardous: No.

Marine pollutant: No.

14.6. Special Precautions for User

EMS: F-D, S-U

14.7. Transport in bulk according to Annex 11 of MARPOL73/78 and the IBC code

SECTION 15: Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Statutory instruments: The Aerosol Dispensers (Amendment) Regulations 2014 No. 1130.

Guidance: Workplace Exposure Limits EH40.
Introduction to Local Exhaust Ventilation HS(G)37.

EU legislation: The Aerosol Dispensers Directive 1975/324 EEC.
Regulation (EC) No. 1272/2008 The Classification, Labelling and Packaging of substances and mixtures Regulations.
Regulation (EC) No. 1907/2006 The Registration, Evaluation, Authorisation and Restriction of Chemicals Regulations (REACH).
2001/95/EC The General Product Safety Directive (GPSD).
Commission Regulation (EU) 2015/830 Requirements for the compilation of safety data sheets (amending REACH).

Authorisations (Title VII Regulation 1907/2006).
No specific authorisations are noted for this product.
Restrictions (Title VIII Regulation 1907/2006).
No specific restrictions of use are noted for this product.

15.2. Chemical safety assessment

SECTION 16: Other Information

Hazard Statements in full:

H220: Extremely flammable gas.
H222: Extremely flammable aerosol.
H225: Highly flammable liquid and vapour.
H304: May be fatal if swallowed and enters airways.
H315: Causes skin irritation.
H336: May cause drowsiness or dizziness.
H411: Toxic to aquatic life with long lasting effects.

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.
The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties.
Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission.